[Time: 3 hours]

[Marks:	80]
---------	-----

N.B. :	1) Question No.	1 is compulsory.			
	2) Attempt any t	hree questions from re	emaining Five.		
	3) Assume suital	ole Data wherever nec	essary.		
	4) Justify your ar	nswers with diagrams	and graphs.		
Q.1	Write short	notes on any four:-			20
		of ash disposal.			
		atic precipitator.			
		and radioactive decay	√.		
		l rankine cycle.			
	v) Auvanta	ges of combined cycle	e power plants.		
Q.2 (a)	Prove that e	fficiency of power pla	ant will be maxim	um at load where heat	10
		to incremental heat ra			
Q.2 (b)	Installed cap	pacity is 200 MW, and is 280 lac, annual	nnual load factor	from power plant if is 0.4, capital cost of lac and interest and	06
Q.2 (c)	discharge is		efficiency is 88	m at 200 r.p.m. The 8 % determine power	04
Q.3(a)				nces linear changes in	08
	load such the	at its daily load curve	is identified as fo	llows	
	Time	Load (MW)	Time	Load(MW)	
	12 PM	24	12.30 PM	48	
	2 AM	12	1 PM	60	

Plot the chronological and load duration curve for the system, find the load factor and utilization factor.

5 PM

6 PM

12 PM

60

84

24

Q.3(b)	Describe in-plant coal handling scheme.	08
Q.3(c)	Explain working of saddle siphon spillway.	04

6 AM

8 AM

12 AM

12

60

60

20

Q.4 (a)	The nature of the load required for 24 hours and thermal efficiencies of	12
	the plant at the respective loads are as follows:	

Time period	Load(MW)	Thermal efficiency
10 AM - 6 PM	120	32%
6 PM - 8 PM	60	24%
8 PM - 12 AM	30	15%
12 AM – 6 AM	15	10%
6 AM – 10 AM	75	25%

- i) Find total input to thermal plant if the load is supplied by the Single thermal plant only.
- i) If the above load is taken by combined thermal and hydro power Plants then find the % saving in the input to the plant.

 Take Thermal efficiency at full load = 32 %
- ii) Find overall efficiencies in both cases.

In hydraulic plant pump efficiency is 82% and turbine efficiency is 92%.

- Q.4 (b) What is depreciation? Explain different methods to calculate depreciation 08 cost.
- Q.5 (a) A gas turbine unit with pressure ratio of 6:1 and maximum cycle temperature of 610 0 C, has the isentropic efficiencies of the compressor and turbine; 0.8 and 0.82 respectively. Calculate the power o/p in kW of an electric generator geared to the turbine when air enters compressor at 15 0 C at the rate of 16 kg/s. Take Cp = 1.005 kJ/kg K and $\gamma = 1.4$ for compression and Cp = 1.005 kJ/kg K and $\gamma = 1.3$ for expansion process.
- Q.5 (b) What are the methods of reducing the wheel or rotor speed of steam turbines?
- Q.6 Answer any Four:
 - i) Classify nuclear reactors.ii) Write short note on selection of type of dam.
 - iii) Compare steam power plant and hydroelectric power
 - iii) Compare steam power plant and hydroelectric power plant.iv) Write short note on Spreader stoker.
 - v) What is chain reaction? What is significance of multiplication Factor?
