		(3 Hours)	[ lotal Marks: 80]	100 S
	1.	Question one is compulsory		2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 -
	2.	Attempt any three from Q.2 to Q.6	\$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$	Z.Y.
	3.	Assume data wherever necessary		
	4.	Figure to the right indicate full marks.		
Q.1	Attemp	ot any four of the following		20
	a)	Write a note on design of rectangular tank.		100
	b)	State the procedure for spherical shell subjected to a	n external pressure.	8
	c)	Draw a neat sketch of Pressure vessel showing all th	e welded category joints.	
	d)	Write a note agitator and its application.		
	e)	Write a note on limphet coil jacket	2	
Q.2	a)	Calculate the thickness of ellipsoidal head (2:1) for f	following design data input.	12
		Material of construction – SA 515 gr 70		
		Design Temperature – 400°c.		
		Design Pressure – 20 bar		
		Inside diameter – 2000 mm		
		Height – 3000 mm	A B B	
		Corrosion allowance – 1.5 mm		
	R	Radiography – Full		
	32 P	Allowable stress – 101 Mpa		
7	\$ 4 V V	Design code – ASME Section VIII, Div 1		
80°C	a)	Explain with reference to pressure vessels		8
V. O. 4	20 50 E	i. Corrosion allowance		
		ii. Welded joint efficiency		
Q.3	a)	Explain ASME section VIII DIV 1.		10
	b)	Write a note on Design of skirt support.		10
2 22 29 20 70 V				
Q.4	a)	A propeller operating at 350 rpm speed in a ves	ssel of 1200 mm diameter with	12
AAA		following data: Design shaft based on equivalent bending and critical speed.		
	A B	Internal pressure in a vessel	$0.3 \text{ N/mm}^2$	
. A C .	My Dick			
		Specific gravity of liquid in vessel	1.1	

**59807** Page **1** of **2** 

## Paper / Subject Code: 53310 / 7)Process Equipment Design

		Power number		30 9 9. C
		Overhang of shaft frombearing support	1500 mm	Y A B
		Shaft material	Steel	
		Permissible shear stress	50 N/mm <sup>2</sup>	
		Elastic limit in tension	250 N/mm <sup>2</sup>	6 7 X
		Modulus of elasticity	2 x 10 <sup>5</sup> N/mm <sup>2</sup>	8 8 E
	b)	State the various types of baffles used in agitator an	d draw a neat sketch of each.	8
Q.5	a)	A cylindrical storage tank with open top has following data.		
		Tank diameter	20 m	
		Tank height	12 m	5,90
		Density of liquid	$1000 \text{ kg/m}^3$	Y
		Permissible stress	165 N/mm <sup>2</sup>	
		Modulus of elasticity	$2 \times 10^5 \text{ N/mm}^2$	
		Corrosion allowance	2 mm	
		Material of construction	Carbon steel	
		Density of MOC	$7850 \text{ kg/m}^3$	
		Design		
		i. Shell plate thickness at various height.		
		ii. Wind girder		
	b)	Discuss with reference to vessel support		10
	2 T	1. Base plate,		
OF A		2. Skirt bearing plate		
Q.6 Att	temp	ot any four		20
	a)	State the types of opening used in pressure vessel as	nd explain any one.	
15,000	b)	Classify agitator		
	c)	Draw shell and tube heat exchanger showing all the	components	
	d)	Write a note on gasket selection and design.		
J. 60, V. 160, V	300	Explain Process Data Sheet and PID		

59807 Page 2 of 2